Mono Bifacial

HORAY | TIER1 BloombergNEF

Solar Galaxy

640–665 Watt

MONO–FACIAL MODULE

- IEC61215: 2021
  IEC61730: 2023
  TUV Rheinland Standard
- Lloyd'S Ariel Re
  Solar Performance Insurance
- ISO9001: 2015
  Quality Management System
- ISO14001:
  Environmental Management System
- CE: Europe Standard
- Inmetro Certificate
- Japan JP-AC
- China Quality Certification Centre
  Solar product certification



KEY FEATURES

MBB Cell
More uniform current collection capability, reducing the current heat loss of the internal cells.

Low Light Features
Higher performance under low light environment.

Higher Output Power
The output power of 132 half-cells Monocrystalline modules is up to 665W.

PID Protection
Ensure the attenuation probability caused by PID phenomenon is minimized.

Harsh Environmental Adaptability
Strict salt spray and ammonia corrosion test by the third party.

Load Capacity
Mechanical load tests including wind load 2400 Pa and snow load 5400 Pa.



HEADQUARTER: HORAY SOLAR CO., LTD.
sales@horaysolar.com www.horaysolar.com +86-510 83580688
NO.30-5, East Yanxin Road, Huishan District, Wuxi 214177 Jiangsu P.R China

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH
info@horaysolar.com www.horaysolar.com
Robert-Bosch-StraBe 27-29,63225 Langen , Germany

MECHANICAL DIAGRAMS



SPECIFICATIONS

Weight	32.5kg
Dimension	2384mm*1303mm*35mm
Cell Dimension	210*105mm
Cell Amount	66*2 pcs
Maximum System Voltage	1500V
Junction Box	IP68
Frame	Aluminum Alloy
Cable	4mm²,+300,-300mm/±1300mm Length can be customized
Connector	MC4 compatible
Application Level	Class A

ELECTRICAL PARAMETERS AT STC

Module Type	HS640-MHG	HS645-MHG	HS650-MHG	HS655-MHG	HS660-MHG	HS665-MHG
Power	640W	645W	650W	655W	660W	665W
Open Circuit Voltage	45.18V	45.38V	45.58V	45.78V	45.98V	46.18V
Short Circuit Current	18.06A	18.11A	18.16A	18.21A	18.26A	18.31A
Maximum Power Voltage	37.21V	37.41V	37.61V	37.81V	38.01V	38.21V
Maximum Power Current	17.20A	17.24A	17.28A	17.32A	17.36A	17.40A
Module Efficiency	20.60%	20.76%	20.92%	21.09%	21.25%	21.41%

* Under Standard Test Conditions (STC) of irradiance of 1000 W/㎡, spectrum AM 1.5 and cell temperature of 25°C.

ELECTRICAL PARAMETERS AT NMOT

Power	483W	487W	491W	495W	499W	503W
Open Circuit Voltage	41.93V	42.11V	42.3V	42.48V	42.67V	43.60V
Short Circuit Current	14.81A	14.85A	14.89A	14.93A	14.97A	15.01A
Maximum Power Voltage	34.49V	34.68V	34.86V	35.05V	35.24V	35.45V
Maximum Power Current	14.03A	14.06A	14.09A	14.13A	14.16A	14.19A

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/㎡, spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

TEMPERATURE CHARACTERISTICS

NMOT	45±2°C	Temp Coefficient of ISC	+0.05%/°C
Temp Coefficient of VOC	-0.28%/°C	Temp Coefficient of Pmax	-0.34%/°C

PACKING CONFIGURATION

Modules/Pallet	31 Pieces	Modules/40'Container	558 Pieces
Packaging Description	18 Pallets, Total=(31+31)x9=558 Pieces		

IV CHARACTERISTICS

HS665-MHG



HS665-MHG



MAXIMUM RATING

Power selection	0~+5W
Measuring uncertainty of Pm	0~±3%
Operating Temperature	-40°C~+85°C
Wind Load/Snow Load	2400pa/5400pa
Fuse Current	30A

12 YEARS Quality Warranty

25 YEARS Power Warranty

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2024 Horay Solar Co.,Ltd. All rights reserved. Specifications included in this datasheet are subject to change without notice.

Version number: MHG_EN_2024_A